

ATLAS COPCO Y1260 HIGH PRESSURE DIESEL COMPRESSOR



General Specifications

Normal working pressure:	35 bar / 507 psi
Pressure range:	21-35bar / 304-507 psi
Dimensions (LxWxH):	5100 x 2250 x 2510mm
Weight (wet):	8000 kg
Fuel tank capacity:	975 L
Fuel consumption (100% load):	97 L/hr
Sound pressure level @ 7m:	81 dBA
Minimum starting temperature:	-25 C °
Maximum ambient temperature:	50 C °
Compressed air connection:	2" BSP

Optional Accessories

Air Dryers	Eliminates condensation
Nitrogen Generators	Produces on-site nitrogen gas from 95% to 99.5% purity
Air Accessories	Air receivers Air heaters After-coolers Boosters Filters Hoses Manifolds
Miscellaneous	Fuel tank Operator Hot air

Features

- DrillAirXpert
- Simple flow and pressure selection controls
- Excellent fuel economy
- Integrated aftercooler
- Fire suppression system
- iAccess
- Emergency Stop
- Lockable isolator
- Portable and easy to transport

Performance

Working Pressure		
bar	psig	
25	363	
35	508	
Free Air Delivery		
L/s	m3/h	cfm
652	2348	1382
579	2083	1226

Air Powered branches and partners nationally
T 1800 247 769
E info@airpoweredservices.com.au
www.airpoweredservices.com.au

airpowered
We know compressed air

